

Frame and suspension

Wheel and tires

Front wheel
and double hump
with inclined-shoulder rim
Size and designation¹⁾
Tire size and designation¹⁾

Rear wheel
with inclined-shoulder rim
and double hump
Size and designation
Tire size and designation¹⁾

2.50 – 18 MT H 2
100/90 V 18
100/90 VR 18*
- TUBELESS -
100/90 V 18
100/90 VR 18*

2.75 – 17 MT H 2
130/90 V 17
140/80 VR 17*
- TUBELESS -
130/90 V 17
140/80 VR 17*

Tire pressures

in bar (lb/in²) with tires cold

	V-tires		VR-tires	
	One-up	Two-up	One-up	Two-up

Road speed	Front	2.25 (32.6)	2.55 (37.0)	2.8 (40.6)	3.00 (43.5)	3.0 (43.5)	3.2 (46.4)
	Rear	2.5 (36.3)	2.7 (39.2)	2.9 (42.0)	3.0 (43.5)	3.0 (43.5)	3.2 (46.4)

Tire tread depths:
Unrestricted
Up to 180 km/h (112 mile/h)
Above 180 km/h (112 mile/h)

Warning:
Note the legal requirements concerning minimum tread depth.

¹⁾ Use them only in pairs
¹⁾ See your BMW dealer or refer to the tire information located under the dualseal for factory-approved brands, models and sizes.